

MATERIAL SAFETY DATA SHEET

1) Identification of the substance/Preparation and Company

1.1 Product Name **SPORT-FIX Quick Tack Carpet Adhesive**

1.2 Use PC1 Adhesive

1.3 Supplier EnviroStik Ltd,
Airfield Industrial Estate
Hixon
Stafford
ST18 OPF
England
Tel: (01889) 271751

2) Hazards Identification

2.1. Classification of the substance or mixture

Classification under CHIP: Xn: R20; Xi: R36/37/38; Xn: R40; Sens.: R42/43; Xn: R48/20

Classification under CLP: Carc. 2: H351; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 2: H373; STOT SE 2: H371; -: EUH204

Most important adverse effects: Harmful by inhalation. Irritating to eyes, respiratory system and skin. Limited evidence of a carcinogenic effect. May cause sensitisation by inhalation and skin contact. Harmful: danger of serious damage to health by prolonged exposure through inhalation.

2.2. Label elements

Label elements under CLP:

Hazard statements: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H351: Suspected of causing cancer.

H371: May cause damage to organs.

H373: May cause damage to organs. through prolonged or repeated exposure.

EUH204: Contains isocyanates. May produce an allergic reaction.

Signal words: Danger

Hazard pictograms: GHS07: Exclamation mark GHS08: Health hazard



Precautionary statements: P260: Do not breathe.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P304+341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P308+313: IF exposed or concerned: Get medical assistance.

P309+311: IF exposed or if you feel unwell: Call a POISON CENTER or doctor.

Label elements under CHIP:



Hazard symbols: Harmful.

Risk phrases: R20: Harmful by inhalation.
R36/37/38: Irritating to eyes, respiratory system and skin.
R40: Limited evidence of a carcinogenic effect.
R42/43: May cause sensitisation by inhalation and skin contact.
R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Safety phrases: S23: Do not breathe vapour.
S36/37: Wear suitable protective clothing and gloves.
S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
S63: In case of accident by inhalation, remove casualty to fresh air and keep at rest.

Precautionary phrases: Contains isocyanates. See information supplied by the manufacturer.
Can become flammable in use

2.3. Other hazards

PBT: This substance is not identified as a PBT substance.

3) Composition/Information on Ingredients

3.2. Mixtures

Hazardous ingredients:

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

- REACH registered number(s): 01-2119457014-47-0000

EINECS 202-966-0

CAS 101-68-8

CHIP Classification Xn: R20; Xi: R36/37/38; Xn: R40; Sens.: R42/43; Xn: R48/20

CLP Classification - Carc. 2: H351; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317; STOT SE 2: H371; STOT RE 2: H373

Percent 30-50%

DICHLOROMETHANE

- REACH registered number(s): 01-2119480404-41-

EINECS 200-838-9

CAS 75-09-2

CHIP Classification Xn: R40

CLP Classification Carc. 2: H351

Percent 10-30%

ETHYL ACETATE

- REACH registered number(s): 01-2119475103-46

EINECS 205-500-4

CAS 141-78-6

CHIP Classification F: R11; Xi: R36; -: R66; -: R67

CLP Classification Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066

Percent 10-30%

4) First Aid Measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Remove from skin with paper towel. Wash effected area thoroughly with soap and water. Seek medical advise if symptoms persist.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Onset of symptoms may be delayed.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

5) Fire Fighting Measures

5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6) Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce a spark.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

7) Handling and Storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): adhesive

8) Exposure Controls/Personal Protection

8.1. Control parameters

Workplace exposure limits:

8 hour TWA 0.02 mg/m³

15 min. STEL 0.07 mg/m³

Hazardous ingredients:

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

8 hour TWA 0.02 mg/m³

15 min. STEL 0.07 mg/m³

DICHLOROMETHANE

8 hour TWA 350 mg/m³

15 min. STEL 1060 mg/m³

ETHYL ACETATE

8 hour TWA 200 ppm

15 min. STEL 400 ppm

8.1 DNEL/PNEC Values

DNEL/PNEC No data available

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: If exposure levels are likely to be exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level exposures, compressed airline breathing apparatus should be used.

Hand protection: Impermeable gloves. Avoid skin contact. For repeated exposure use Viton or 4H chemical gloves, for low exposure use nitrile gloves. The user has a legal responsibility to carry out a COSHH risk assessment to determine the correct glove.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Environmental: No special requirement.

9) Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State: Liquid
Colour: Colourless
Odour: Characteristic odour
Evaporation rate: Fast
Oxidising: Non-oxidising (by EC criteria)
Solubility in water: Reacts with water.
Viscosity: Viscous
Boiling point/range°C: 77
Autoflammability°C: 460

9.2. Other information

No data available

10) Stability and Reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

11) Toxicological Information

11.1. Information on toxicological effects

Hazardous Ingredients:

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

| | | | | |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 2200 | mg/kg |
| ORL | RAT | LD50 | 9200 | mg/kg |

DICHLOROMETHANE

| | | | | |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 4770 | mg/kg |
| ORL | RAT | LD50 | 5350 | mg/kg |
| SCU | MUS | LD50 | 6460 | mg/kg |

ETHYL ACETATE

| | | | | |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 4100 | mg/kg |
| ORL | RAT | LD50 | 5620 | mg/kg |
| SCU | RAT | LDLO | 5 | gm/kg |

Relevant effects for mixture:

| Effect | Route | Basis |
|--------------------------|-------------|-----------------------|
| Acute toxicity (harmful) | INH | Hazardous: calculated |
| Irritation | OPT INH DRM | Hazardous: calculated |
| Sensitisation | INH DRM | Hazardous: calculated |
| Repeated dose toxicity | INH | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: There may be mild irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Onset of symptoms may be delayed.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: Not applicable.

12) Ecological Information

12.1. Toxicity

Ecotoxicity values: No data available

12.2. Persistence and degradability

Persistence and degradability: Biodegradable in part only.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Volatile.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Not applicable

13) Waste Disposal

13.1. Waste treatment methods

Disposal operations: Wet waste: Arrange for disposal by a licenced waste disposal company.

Disposal of packaging: Arrange for disposal by a licenced waste disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14) Transport Information

14.1. UN number

UN number: UN2810

14.2. UN proper shipping name

Shipping name: TOXIC LIQUID, ORGANIC, N.O.S. (DICHLOROMETHANE)

14.3. Transport hazard class(es)

Transport class: 6.1

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions

Tunnel code: E

Transport category: 2

15)Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010. This MSDS is in accordance with CHIP which implements two European Community Directives: The Dangerous Substances Directive (DSD EU directive 67/548/EEC)

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

16)Other Information

Other information

Other information:

This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010, using the current safety information supplied by the distributors of the component materials. This leaflet may contain inappropriate information under particular conditions of use.

Phrases used in s.2 and 3:

EUH066: Repeated exposure may cause skin dryness or cracking.

EUH204: Contains isocyanates. May produce an allergic reaction.

H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H371: May cause damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H373: May cause damage to organs <or state all organs affected, if known> through

prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

R11: Highly flammable.

R20: Harmful by inhalation.

R36/37/38: Irritating to eyes, respiratory system and skin.

R36: Irritating to eyes.

R40: Limited evidence of a carcinogenic effect.

R42/43: May cause sensitisation by inhalation and skin contact.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer:

This product is for professional use only and should be used as directed by EnviroStik Ltd. For further information consult the application data sheet.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The company shall not be held liable for any damage resulting from handling or from contact with the above product.