



# Seaming Tape RTX Grade

## Reinforced Fabric/Mesh Laminate

### INTRODUCTION

Seam jointing tape RTX is a high strength textile laminate, specially designed to assist in reaching the IRB joint performance specification for artificial grass surfaces used for Rugby.

The tape is a special construction, primarily for use with EnviroStik Ultra-Fix polyurethane adhesive. It will form strong bonds when seam jointing the third generation long pile artificial rubber/sand-filled carpets used in the surfacing of sports areas, particularly for rugby and GAA

The tape consists of a strong black woven polypropylene mesh fabric laminated to a white polyester interface. This construction is designed to impart high strength into the bonding medium and thus prevent any chance of joint failure under the severe playing characteristics, associated with rugby and football.

### FEATURES

- High strength reinforced tape designed to maximise seam joint tensile strength, required by the IRB performance specification.
- Lays flat and rolls out straight when used on substrate.
- Suitable for use in ES300 Seam-Rite adhesive applicator.

### METHOD OF USE

IMPORTANT: Before embarking on any work involving Seaming Tape RTX the Health and Safety Data Sheet should be carefully studied by those carrying out the work.

### APPLICATION

Seaming Tape RTX is designed for use in conjunction with Ultra-Fix two component polyurethane adhesive. The correct amount of this adhesive is applied by notched applicator to the tape surface allowing a margin of 2 cm to 3 cm at either side. Ensure that a minimum of 12 cm of the carpet edge is firmly pressed into the wet adhesive. For more detailed instructions on the use of this product see the Data Sheet for Ultra-Fix Adhesive.

### PRODUCT CHARACTERISTICS

<b>Colour &amp; Form:</b>	Black woven polypropylene mesh laminated to a non woven polyester geo-textile.	
<b>Bonding Medium:</b>	Spunbonded polyester textile.	
<b>Roll Sizes:</b>	Length:	100 m.
	Width:	300 mm.
	Thickness:	1.00 mm.
<b>Tensile Strength:</b>	>3000N/100 mm (EN12228 Method 1)	
<b>Peel Strength:</b>	> 100N/100 mm (EN12228 Method 2) (when used in combination with Ultra-Fix Seam jointing adhesive)	
<b>Weight:</b>	390 g/m <sup>2</sup> . (12 kilos per roll)	
<b>Storage:</b>	0 to 30°C.	
<b>Packaging:</b>	Rolls are offered palletised	

This leaflet is for general guidance only and may contain inappropriate information under particular conditions of use. The company cannot accept any responsibility for loss or damage that may result from the use of this information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm the suitability of this product by their own tests.