



Seaming Tape RTX Grade

Reinforced Fabric/Mesh Laminate

INTRODUCTION

Seam jointing tape RTX is a high strength textile laminate, specially designed to assist in reaching the IRB joint performance specification for artificial grass surfaces used for Rugby.

The tape is a special construction, primarily for use with Envirostik Ultra-Fix polyurethane adhesive. It will form strong bonds when seam jointing the third generation long pile artificial rubber/sand-filled carpets used in the surfacing of sports areas, particularly for rugby and GAA.

The tape consists of a strong, polyester fabric laminate. This construction is designed to impart high strength into the bonding medium and thus prevent any chance of joint failure under the severe playing characteristics, associated with rugby and football.

FEATURES

- High strength reinforced tape designed to maximise seam joint tensile strength, required by the IRB performance specification.
- Lays flat and rolls out straight when used on substrate.
- Suitable for use in ES300 Seam-Rite adhesive applicator.
- Suitable for use in the Envirostik ES300 and ES400 Seam-Rite adhesive applicator machines.

METHOD OF USE

IMPORTANT: Before embarking on any work involving Seaming Tape RTX the Health and Safety Data Sheet should be carefully studied by those carrying out the work.

APPLICATION

Seaming Tape RTX is designed for use in conjunction with Ultra-Fix two component polyurethane adhesive. The correct amount of this adhesive is applied by notched applicator to the tape surface allowing a margin of 2cm to 3cm at either side. Ensure that a minimum of 12cm of the carpet edge is firmly pressed into the wet adhesive. For more detailed instructions on the use of this product see the Data Sheet for Ultra-Fix Adhesive.

PRODUCT CHARACTERISTICS

Colour & Form:	White polyester fabric laminated structure
Bonding Medium:	Spunbonded polyester textile
Roll Size:	Length: 200m Width: 300mm & 400mm Thickness: 0.45mm
Weight:	274g/m ²
Tensile Strength:	>3500N/100mm (EN12228 Method 1)
Peel Strength:	>100N/100mm (EN12228 Method 2) (when used in combination with Ultra-Fix Seam jointing adhesive)
Storage:	0°C to +30°C
Packaging:	Rolls are offered palletised

This leaflet is for general guidance only and may contain inappropriate information under particular conditions of use. The company cannot accept any responsibility for loss or damage that may result from the use of this information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm the suitability of this product by their own tests.